

Package: fgeo.x (via r-universe)

August 21, 2024

Title Access Small ForestGEO Datasets For Examples

Version 1.1.4.9000

Description Access small example datasets from Luquillo, a ForestGEO site in Puerto Rico
(<https://forestgeo.si.edu/sites/north-america/luquillo>).

License GPL-3

URL <https://github.com/forestgeo/fgeo.x>

BugReports <https://github.com/forestgeo/fgeo.x/issues>

Depends R (>= 3.2)

Imports memoise (>= 1.1.0), utils

Suggests spelling (>= 2.1), testthat (>= 2.1.1)

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 6.1.1

Repository <https://forestgeo.r-universe.dev>

RemoteUrl <https://github.com/forestgeo/fgeo.x>

RemoteRef HEAD

RemoteSha cbbe8cb2001c749939cd20e7871a760a398e4c95

Contents

datasets	2
download_data	2
example_path	3

Index	5
--------------	----------

datasets	<i>Access data via library(fgeo.x) or fgeo.x::<dataset-name>.</i>
----------	---

Description

These are small datasets for examples, with no value for research. They have been adapted from the package [fgeo.data](#).

See Also

Other datasets: [download_data](#), [example_path](#)

Examples

```
str(elevation)
str(habitat)
str(stem5)
str(stem6)
str(tree5)
str(tree6)
str(tree6_3species)
str(vft_4quad)
```

download_data	<i>Access data stored online.</i>
---------------	-----------------------------------

Description

Access data stored online.

Usage

```
download_data(x, destfile = NULL)
```

Arguments

x	A string giving the name of the dataset to download. The name of any dataset listed here (without the extension).
destfile	a character string (or vector, see url) with the name where the downloaded file is saved. Tilde-expansion is performed.

Value

A dataset.

See Also

[utils::download.file\(\)](#)

Other datasets: [datasets](#), [example_path](#)

Examples

```
# Not running CRAN checks (may take longer than the allowed run time limit)

# Defaults to read data
# The first call is memoised
system.time(download_data("unique_id"))
# Subsequent calls use the memoised data, so takes no time
system.time(download_data("unique_id"))

download_data("unique_id")

# Can download data to a destination file given by `destfile`
tmp <- tempfile()
download_data("unique_id", destfile = tmp)
load(tmp)
unique_id

available_data <- "https://github.com/forestgeo/fgeo.data/tree/master/data"
if (interactive()) browseURL(available_data)
```

example_path	<i>Access data stored in system files.</i>
--------------	--

Description

example_path() mostly wraps system.file(..., package = "fgeo.x").

Usage

```
example_path(path = NULL)
```

Arguments

path Name of file or directory. If NULL, the example files and directories will be listed.

Value

A character string.

See Also

Other datasets: [datasets](#), [download_data](#)

Examples

```
example_path()  
dir(example_path("rdata"))  
example_path("taxa.csv")  
str(read.csv(example_path("taxa.csv")))
```

Index

* datasets

datasets, [2](#)

download_data, [2](#)

example_path, [3](#)

datasets, [2](#), [3](#), [4](#)

download_data, [2](#), [2](#), [4](#)

elevation (datasets), [2](#)

example_path, [2](#), [3](#), [3](#)

habitat (datasets), [2](#)

stem5 (datasets), [2](#)

stem6 (datasets), [2](#)

tree5 (datasets), [2](#)

tree6 (datasets), [2](#)

tree6_3species (datasets), [2](#)

utils::download.file(), [3](#)

vft_4quad (datasets), [2](#)